

1. Report No. MR 2011-01	2. Report Date February 2020	3. Contract No. N/A	4. Project No. SER-2-003(018)008
5. Title and Subtitle Evaluation of "Safety Edge" on Asphalt Pavement		6. Report Type Click on link to open report. Work Plan <input type="checkbox"/> Construction <input type="checkbox"/> Evaluation <input type="checkbox"/> <u>Final</u> <input checked="" type="checkbox"/>	7. Project No. MER-2-011(029)041 8. Project No. MER-2-011(030)045 9. Project No. MER-2-013(044)249 10. Project No. MER-2-046(041)014
11. Author(s)/Principal Investigator(s) TJ Murphy			
12. Performing Organization Name and Address NDDOT M+R <input checked="" type="checkbox"/> North Dakota DOT NDDOT OTHER* <input type="checkbox"/> Materials and Research Division NDSU <input type="checkbox"/> 300 Airport Road UND <input type="checkbox"/> Bismarck ND 58504-6005 UGPTI <input type="checkbox"/> OTHER* <input type="checkbox"/> *see supplementary notes		13. Sponsoring Agency Name and Address North Dakota DOT Materials and Research Division 300 Airport Road Bismarck ND 58504-6005	
14. Supplementary Notes			
15. Abstract Purpose and Need The focus of FHWA's "Every Day Counts (EDC) "initiatives are to identify and deploy innovative techniques targeted at shortening project delivery, enhancing the safety of roadways, and protecting the environment. Drivers who drift from the roadway need a method to safely transition back onto the paved surface. It is reported that some states construct their asphalt pavements using a vertical edge at the outside edges of the pavement. An errant driver leaving the paved surface may find it difficult to return to the paved surface, and the attempt may result in a serious accident. Soil or granular materials may be brought up to the top of the pavement to create a transition; however, erosion or vehicular damage to this area may re-expose the vertical pavement edge – creating a maintenance and ultimately safety issue. The construction of a wedge-shaped transition at the pavement edge has been shown to be effective in allowing an errant driver to safely return to the paved surface. FHWA sponsored research has shown the 30-degree angle of the "Safety Edge" to be the optimal angle to allow drivers to return to the roadway safely. Objective The objective of this project is to evaluate the construction of the <i>Safety Edge</i> using a FHWA provided "safety shoe" device that forms and consolidates the pavement edge. Scope The NDDOT Design Division has identified five asphalt paving projects scheduled for construction in the Valley City District during the 2011-2012 seasons. Requirements for the construction of the <i>Safety Edge</i> and use of the "safety shoe" were incorporated into the bid and construction documents by plan details and special provision. The "safety shoe" being provided by FHWA is the <i>Ramp Champ</i> manufactured by Advant-Edge Paving Equipment, LLC Summary Over the 2011-2012 construction seasons NDDOT has constructed five projects totaling 3.795 miles of roadway with the 30° Safety Edge design. The Pavement Ramp Champ device was used on all 5 projects by the same contractor BSP to successfully produce a safe traversable pavement edge. Average Angle produced with the Ramp Champ device on all five projects combined was 26.2° with a standard deviation of 4.0°. The three control projects were emergency grade raises constructed allowing the contractor to install the edge by their own methods. The contractor chose to use a slough box. Average Angle produced with this method was 20.9° with a standard deviation of 4.5°. Both methods of producing the 30° Safety edge had comparable results.			
16. Key Words Ramp Champ Safety Edge Pavement Edge EDC(Every Day Counts)	17. Distribution Statement No restrictions. This document is available by clicking this link: North Dakota Department of Transportation Materials and Research Division: 300 Airport Road Bismarck, ND 58504-6005	18. No. of Pages 85	19. File type Pdf