D-754-21 REFLECTORIZED DELINEATORS - DIVIDED HIGHWAY Reflector (note 3) Delineator Details Type A, B, and C Installation: Install posts along the right shoulder line, in the direction of travel, unless shown Reflectors: Use reflector of the same color as the adjacent pavement marking with a 0.080 inch minimum thickness sign backing material. 8' clearance to finished shoulder Sign and Delineator shoulder Aluminum Post Detail Alternate: As an alternate, use one unit band consisting of two yellow stripes separated by a 2" black Steel Post Detail Approx. 0.88 lbs/ft Approx. 2.0 lbs/ft — ⊈ of roadway Installation (Type A, B, and C) Edge of traffic lane elevation - Bottom of ditch Section A - A (1) Use fasteners that are a minimum $\frac{1}{4}$ " diameter. Use double headed rivet or other non-rust vandal resistant fastener - Fastener (note 1) Median Crossovers (2) Drill only those holes required to attach the number of reflectors on that post, or drill all the posts the same so that any number of reflectors may be added. Signing and Delineation system (3) Mount reflector facing traffic at an angle of 90° away from oncoming traffic. $\mbox{(4)}$ Median width may vary. Place sign and delineator assembly in the median crossover an equal distance from each roadway. (5) Include all costs for materials, labor, and equipment to install single sided type A delineators in the unit price bid for "Delineators-Type A-Single Sided." Include all costs for materials, labor, and equipment to install single sided type B, type C, type D, and type E delineators in the unit price bid for "Delineators-Type B", "Delineators-Type C", "Delineators-Type C", and "Delineators-Type E." Type A, Type B, and Type C Delineator Attachment Detail 1½" 3" wide white/yellow band 3" wide white/yellow band -3" wide yellow band above edge traffic lane Yellow reflective 1½" Main line Single Sided Reflector Type A (Type A delineator) Type D Type E Ramps Two reflectors Median Median (Type B delineator) Two reflectors (Delineators-Type E) One reflector (Delineators-Type D) NORTH DAKOTA Narrow Bridges DEPARTMENT OF TRANSPORTATION - 6" dia. -Three reflectors 12/16/22 (Type C delineator) REVISIONS DATE 3" wide yellow **PROFESSIONAL** 2" wide black U-type Post U-type Post U-type Post PE-4683 (Delineator-Type A-Single Sided) (Delineators-Type B) (Delineators-Type C)

3" wide yellow

Alternate Type E delineator

12/16/22